

FastBack™ Backing System

Reduces finishing time with no exposed fasteners on the face of the product.

The FastBack™ backing system features a universal design that works with studs in either direction—concealing fasteners on the face of the product. The system creates an interlocked design between the stud and track for baseboard backing installations; and a cutaway design allows backing and bracing to be installed all the way to the floor. Optional pre-cut and fire-rated D-Blaze® or FlamePRO® Wood Backing is sized to fit 12," 16" and 24" o.c. spacing and can be used with the FBBC5 or FBBC10 clip. Available for overnight delivery. FBBC5-2X, 162-FBBC5-2X and 200-FBBC5-2X are designed to support traditional 2X lumber.

INSTALLATION

Rotate the FastBack clip over the flange of the stud until it sits flush. Fasten into place using drywall screws in the pre-drilled holes. Place wood onto tabs and fasten into place using standard drywall screws.



FastBack™ Backing System

Product code	Stud Flange (F)	Height (H)	Backing (B)	Packaging Pcs./Carton
FBBC5	1-1/4"	5-1/8"	3/4" (5 ply)	100
FBBC10	1-1/4"	10-1/4"	3/4" (5 ply)	100
FBBC5-2X	1-1/4"	5-1/8"	3/4" (5 ply)	100
162-FBBC-2X	1-5/8"	5-1/8"	1-1/2" (2X lumber)	100
200-FBBC5-2X	2"	5-1/8"	1-1/2" (2X lumber)	100

Wood Backing

Product code	Height (in)	Length (in)	Packaging Pcs./Skid
5FBW12	5-1/8"	10-1/2"	720
5FBW16	5-1/8"	14-1/2"	540
5FBW24	5-1/8"	22-1/2"	360
10FBW12	10-1/4"	10-1/2"	720
10FBW16	10-1/4"	14-1/2"	540
10FBW24	10-1/4"	22-1/2"	360

U.S. Patent No. 7,882,676 of Jeffrey Thomas Ellis

D-Blaze® is a registered trademark of Viance, LLC

FlamePRO® is a registered trademark of Koppers Performance Chemicals, Inc.

FlamePRO® Fire Retardant complies with or has been granted the following:

- UL GREENGUARD Gold Certification – UL 2818
 - ICC ESR-4244
 - AWPA E12, AWPA M4, AWPA P50, AWPA T1 standard
 - Cal Fire Certified
 - American Institute of Architects Approved
 - ASTM 2768
 - ASTM D3201, D5516, D5664, E84, E119, 2768, D6305, D6841
 - AWPA T1
 - AWPA UC-1
 - Class A FRT wood
 - UL Recognized Component
 - NFPA 703, 101 Life Safety Code
 - City of Los Angeles Building Code
 - City of Los Angeles Residential Code
 - National Building Code of Canada
 - One & two hour tested wall assemblies
 - 50-year warranty
 - UL Classified with an FR-S Rating for flame spread and smoke development values of 25 or less
- (All are subject to revision, re-examination)

D-Blaze® Fire Retardant or D-Blaze® FRT Wood complies with or has been granted the following:

- ASTM E84
 - ASTM D3201
 - ASTM D5516
 - ASTM D5664
 - Underwriters Laboratories Classified
 - UL Class A (Class 1) with FR-S Rating CAN/ULC S102 & S102.2
 - GREENGUARD Gold Certified
 - National Fire Protection Association (NFPA 255)
 - City of Los Angeles Research Report: RR24502 in accordance with ICC-ES ESR 2645
 - New York City Building Code (MEA Numbers 406-87 and 407-87)
 - National Building Code of Canada
 - AWPA Standardized (P50, U1, UCFA) Interior Type A-High Temperature (HT) FRTW
 - California Department of Forestry and Fire Protection CSFM BML Listings for D-Blaze Plywood and Lumber
 - ICC-ES ESR-2645
 - 50-year warranty
- (All are subject to revision, re-examination)

